



迷你型快速接线端子系列

MINI FAST TERMINAL



型号 Model	221-102		221-103		221-105	
外形尺寸 Outline size						
参考标准 Reference standard	UL	IEC	UL	IEC	UL	IEC
额定电压 Rated voltage V	660	450	660	450	660	450
额定电流 Rated current A	20	32	20	32	20	32
导线线径 Wire diameter AWG/mm ²	24-12AWG	0.14(0.2)-4mm ²	24-12AWG	0.14(0.2)-4mm ²	24-12AWG	0.14(0.2)-4mm ²
耐电压 Voltage resistance kV	2.5		2.5		2.5	
机械性能 Mechanical properties						
环境温度 Ambient temperature °C	-40°C~+105°C		-40°C~+105°C		-40°C~+105°C	
剥线长度 Strip length mm	11		11		11	
长×宽×高 L/W/H	18.2×13×9.8		18.2×18.6×9.8		18.2×29.9×9.8	
极数 The number of poles p	2		3		5	
材质和电镀 Material and plating						
塑件 Plastic parts	PC, UL94,V-2		PC, UL94,V-2		PC, UL94,V-2	
弹片 Shrapnel	不锈钢 Stainless steel		不锈钢 Stainless steel		不锈钢 Stainless steel	
触点材料 Contact material	电解铜镀镍锡 Electrolytic copper nickel tin		电解铜镀镍锡 Electrolytic copper nickel tin		电解铜镀镍锡 Electrolytic copper nickel tin	



型号 Model	EU2.5-412(2孔)		EU2.5-413(3孔)		EU2.5-414(4孔)	
外形尺寸 Outline size						
参考标准 Reference standard	UL	IEC	UL	IEC	UL	IEC
额定电压 Rated voltage V	660	450	660	450	660	450
额定电流 Rated current A	20	32	20	32	20	32
导线线径 Wire diameter AWG/mm ²	18-14AWG	0.5-2.5mm ²	18-14AWG	0.5-2.5mm ²	18-14AWG	0.5-2.5mm ²
耐电压 Voltage resistance kV	2.5		2.5		2.5	
机械性能 Mechanical properties						
环境温度 Ambient temperature °C	-40°C~+105°C		-40°C~+105°C		-40°C~+105°C	
剥线长度 Strip length mm	11		11		11	
长×宽×高 L/W/H	16.7×10×5.8		16.7×14×5.8		16.7×18×5.8	
极数 The number of poles p	2		3		4	
材质和电镀 Material and plating						
塑件 Plastic parts	PC, UL94,V-2		PC, UL94,V-2		PC, UL94,V-2	
弹片 Shrapnel	不锈钢 Stainless steel		不锈钢 Stainless steel		不锈钢 Stainless steel	
触点材料 Contact material	电解铜镀镍锡 Electrolytic copper nickel tin		电解铜镀镍锡 Electrolytic copper nickel tin		电解铜镀镍锡 Electrolytic copper nickel tin	

迷你型快速接线端子系列

MINI FAST TERMINAL



型号 Model	EU2.5-415(5孔)		EU2.5-422		EU2.5-424	
外形尺寸 Outline size						
参考标准 Reference standard	UL	IEC	UL	IEC	UL	IEC
额定电压 Rated voltage V	660	450	660	450	660	450
额定电流 Rated current A	20	32	20	32	20	32
导线线径 Wire diameter AWG/mm ²	18-14AWG	0.5-2.5mm ²	18-14AWG	0.5-2.5mm ²	18-14AWG	0.5-2.5mm ²
耐电压 Voltage resistance kV	2.5		2.5		2.5	
机械性能 Mechanical properties						
环境温度 Ambient temperature °C	-40℃~+105℃		-40℃~+105℃		-40℃~+105℃	
剥线长度 Strip length mm	11		11		11	
长×宽×高 L/W/H	16.7×22×5.8		16×11×5.5		16×10×11	
极数 The number of poles p	5		2		4	
材质和电镀 Material and plating						
塑件 Plastic parts	PC, UL94,V-2		PC, UL94,V-2		PC, UL94,V-2	
弹片 Shrapnel	不锈钢 Stainless steel		不锈钢 Stainless steel		不锈钢 Stainless steel	
触点材料 Contact material	电解铜镀镍锡 Electrolytic copper nickel tin		电解铜镀镍锡 Electrolytic copper nickel tin		电解铜镀镍锡 Electrolytic copper nickel tin	



型号 Model	EU2.5-426(6孔)		EU2.5-428(8孔)	
外形尺寸 Outline size				
参考标准 Reference standard	UL	IEC	UL	IEC
额定电压 Rated voltage V	660	450	660	450
额定电流 Rated current A	20	32	20	32
导线线径 Wire diameter AWG/mm ²	18-14AWG	0.5-2.5mm ²	18-14AWG	0.5-2.5mm ²
耐电压 Voltage resistance kV	2.5		2.5	
机械性能 Mechanical properties				
环境温度 Ambient temperature °C	-40℃~-+105℃		-40℃~-+105℃	
剥线长度 Strip length mm	11		11	
长×宽×高 L/W/H	16.7×14×5.8		16.7×18×5.8	
极数 The number of poles p	3		8	
材质和电镀 Material and plating				
塑件 Plastic parts	PC，UL94,V-2		PC，UL94,V-2	
弹片 Shrapnel	不锈钢 Stainless steel		不锈钢 Stainless steel	
触点材料 Contact material	电解铜镀镍锡 Electrolytic copper nickel tin		电解铜镀镍锡 Electrolytic copper nickel tin	



PTC快速接线端子系列

PTC FAST TERMINAL SERIES



型号 Model	222-102(2孔)		222-103(3孔)		222-105(5孔)		
外形尺寸 Outline size							
参考标准 Reference standard	UL	IEC	UL	IEC	UL	IEC	
额定电压 Rated voltage	V	660	450	660	450	660	450
额定电流 Rated current	A	20	32	20	32	20	32
导线线径 Wire diameter	AWG/mm ²	24-12AWG	0.14(0.2)-4mm ²	24-12AWG	0.14(0.2)-4mm ²	24-12AWG	0.14(0.2)-4mm ²
耐电压 Voltage resistance	kV	2.5		2.5		2.5	
机械性能 Mechanical properties							
环境温度 Ambient temperature	℃	-40℃~+105℃		-40℃~+105℃		-40℃~+105℃	
剥线长度 Strip length	mm	11		11		11	
长×宽×高 L/W/H		20.5×12.4×14.5		20.5×17×14.5		20.5×26.6×14.5	
极数 The number of poles	p	2		3		5	
材质和电镀 Material and plating							
塑件 Plastic parts		PA66		PA66		PA66	
弹片 Shrapnel		不锈钢 Stainless steel		不锈钢 Stainless steel		不锈钢 Stainless steel	
触点材料 Contact material		电解铜镀镍锡 Electrolytic copper nickel tin		电解铜镀镍锡 Electrolytic copper nickel tin		电解铜镀镍锡 Electrolytic copper nickel tin	



型号 Model	773-102(黄色/透明)	773-104(橙色/透明)	773-106(紫色/透明)
外形尺寸 Outline size			
额定电压 Rated voltage V	400	400	400
额定电流 Rated current A	24	24	24
导线线径 Wire diameter mm ²	0.75-2.5	0.75-2.5	0.75-2.5
耐电压 Voltage resistance kV	2.5	2.5	2.5
机械性能 Mechanical properties			
电位数量 Potential quantity °C	1	1	1
剥线长度 Strip length mm	12	12	12
长×宽×高 L/W/H	19.5×9.4×13.1	19.5×13×13.1	19.5×18.5×13.1
极数 The number of poles p	2	4	6
材质和电镀 Material and plating			
塑件 Plastic parts	PC, UL94,V-2	PC, UL94,V-2	PC, UL94,V-2
弹片 Shrapnel	不锈钢 Stainless steel	不锈钢 Stainless steel	不锈钢 Stainless steel
触点材料 Contact material	电解铜镀镍锡 Electrolytic copper nickel tin	电解铜镀镍锡 Electrolytic copper nickel tin	电解铜镀镍锡 Electrolytic copper nickel tin

PTC快速接线端子系列

PTC FAST TERMINAL SERIES



型号 Model	773-108	773-103(红色/透明)	773-104D(橙色/透明)
外形尺寸 Outline size			
额定电压 Rated voltage	V	400	600
额定电流 Rated current	A	24	35
导线线径 Wire diameter	mm ²	0.75-2.5	0.75-6
耐电压 Voltage resistance	kV	2.5	2.5
机械性能 Mechanical properties			
电位数量 Potential quantity	℃	1	1
剥线长度 Strip length	mm	12	12
长×宽×高 L/W/H		19.5×24×13.1	20.1×33.6×14.2
极数 The number of poles	p	8	4
材质和电镀 Material and plating			
塑件 Plastic parts	PC, UL94,V-2	PC, UL94,V-2	PC, UL94,V-2
弹片 Shrapnel	不锈钢 Stainless steel	不锈钢 Stainless steel	不锈钢 Stainless steel
触点材料 Contact material	电解铜镀镍锡 Electrolytic copper nickel tin	电解铜镀镍锡 Electrolytic copper nickel tin	电解铜镀镍锡 Electrolytic copper nickel tin



型号 Model	224-101(深灰色)	CH-2按压式接线端子	CH-3按压式接线端子
外形尺寸 Outline size			
额定电压 Rated voltage	V	450	600
额定电流 Rated current	A	24	20
导线线径 Wire diameter	mm ²	0.2-2.5	0.2-1.5
耐电压 Voltage resistance	kV	2.5	1.5
机械性能 Mechanical properties			
电位数量 Potential quantity	℃	1	1
剥线长度 Strip length	mm	11	9
长×宽×高 L/W/H	20.5×8.5×15.5	19.5X12.5X13	27X19.5X13
极数 The number of poles	p	2	3
材质和电镀 Material and plating			
塑件 Plastic parts	PA66	PA6	PA6
弹片 Shrapnel	不锈钢 Stainless steel	不锈钢Stainless stell	不锈钢Stainless stell
触点材料 Contact material	电解铜镀镍锡 Electrolytic copper nickel tin	无/NO	无/NO