

PRODUCT IMAGE

PRODUCT PARAMETERS



CBS-001

- Rating: 3A~20A 250V(AC/DC)
- Lamp Voltage: 12V~220V
- Terminal Type: Long Or Short

PRODUCT IMAGE

PRODUCT PARAMETERS



KSD301A-OR2 NC
KSD301B-OR2 NO

- Rating: 10A/16A 250VAC
- Operating Temp: 0~260 °C



CBS-1

- Rating: 3A~25A 250V(AC/DC)
- Button Color: Red or Black



RH-01

- Rating: 2A/3A 250VAC
- Operating Temp: 65~285 °C



CBS-2A

- Rating: 15A~50A 250V(AC/DC)



RY-01

- Rating: 10A/15A 250VAC
- Operating Temp: 65~285 °C



CBS-2P

- Rating: 15A~50A 250V(AC/DC)



TLRS-9700P Plastic
TLRS-9700M Metal

- Rating: 5A 250VAC
- Operating Temp: 40~150 °C



CBS-002

- Rating: 5A~20A 250V(AC/DC)
- Lamp Voltage: 12V~220V



DZ47N-63

- Rating: 10A~63A 250V(AC/DC)
- Material: Bakelite
- Position: 1, 2, 3, 4